

JEXtream®MDM

Workflow For Business Users

Account Setup

- Go to JEXtream.net/contact
- Download the New Organization Workbook

New Organization Workbook

Download the workbook, fill it out, and return it for new JEXtream MDM organization setup.

[Download XLSX](#)

Worksheet 1:

Admin user names/email/organization name

	A	B	C	D
1	Full Name	Email Address	Role	Organization Name
2	John Doe	john.d@acme.com	Organization Admin	Acme inc
3	Jane doe	janed@acme.com	Group Admin	Acme inc

Worksheet 2:

List of IMEIs, Mobile numbers, & Asset tag (if applicable)

	A	B	C	D
1	imei	phone	Device	asset tag
2	358563790012345	9169403356	A50	
3	358563790012346	9169403357	A50	

Worksheet 3:

If you prefer to have different configurations for each device.

If customer has groups and would like to allot devices to groups, please provide that in Worksheet 3.

- GROUP NAME
- IMEI
- MOBILE NUMBER
- ASSET TAG / DESCRIPTION

POLICY CONFIGURATION (Worksheet 3)

USER ENTRY

Model	M	Model Name	RG2100	RG2100	If you have A50 - Select RG2100, A70 - 3100, JEXtream from 1 Mobile - RG2100, or 3100 or select the device you have. If you don't find the device contact - sales@franklinaccess.com
Hotspot Name	M	Device Name	Customizable	Acme Library SG	Asset name or Asset ID
Main Wifi Name	M	This allows you to set the Main Wifi SSID name as the default/factory or create your own	Min 6 char	ACME LIBRARY	SSID you prefer. You can select "Factory" for factory unique values for each IMEI. Password you prefer. You can select "Factory" for factory unique values for each IMEI.
Main Wifi Password	M	This allows you to set the Main Wifi password as the default/factory or create your own	Min 8 char	Love2read	These devices have dual WiFi - 2.4GHz and 5GHz. One is Main and the other is Guest. You have a choice to keep both or turn-off Guest
Guest Wifi Name	M	This allows you to set the Guest Wifi SSID name as the default/factory or create your own	Min 6 char (Off = N/A)	N/A	These devices have dual WiFi - 2.4GHz and 5GHz. One is Main and the other is Guest. You have a choice to keep both or turn-off Guest
Guest Wifi Password	M	This allows you to set the Guest Wifi password as the default/factory or create your own	Min 8 char (Off = N/A)	N/A	These devices have dual WiFi - 2.4GHz and 5GHz. One is Main and the other is Guest. You have a choice to keep both or turn-off Guest
Display Wifi Name and Password	O	Turn on/off the wifi name and password showing on the device display.	0 = Disabled (All Off) 1 = Primary Wifi only 2 = Guest Wifi only 3 = Primary + Guest Wifi (Default = 3)	1	If the GUEST wifi network is off, Display Primary only. There are cases where admin may prefer to turn-off the ssid / pwd from displaying. (Example: Connecting to chrome book)
Product Description	O	Product Description	Customizable	FranklinSG	
Total Wifi Connections	O	Number of connections allowed at one time split between Main and Guest Wifi	10	3	no. of Wifi connections total between Main and Guest Wifi.
Main Wifi Max connections	O	Number of connections allowed at one time on the Main Wifi	Blank = 15	4	
Guest Wifi Max connections	O	Number of connections allowed at one time on the Guest Wifi	Blank = 5 (Off = N/A)	N/A	Ignore if you have chosen to Turn-off Guest
Main Wifi Bands	O	Set supported band at 2.4GHz & 5GHz	2.4GHz or 5GHz (2.4GHz default)	default	Main Wifi Band, Commonly 2.4GHz
Guest Wifi Bands	O	Set supported band at 2.4GHz & 5GHz	2.4 GHz or 5GHz (5GHz default)	N/A	
Data Usage Cycle	O	Monthly or Yearly tracking of data usage	0 = Monthly* (Default) 1 = Yearly	default	Default is monthly. Data will reset monthly

Next Steps

- Email completed workbook to sales@franklinaccess.com
- Are you interested in content filtering? Ask about it in the email.
- Training dates/times - 9AM to 4PM PST - Thursday or Friday
- JEXtream Cloud expert certification (for resellers) - Tuesday 10AM to 3PM One hour course.

Manage Smarter. Deploy Faster. Stay Connected.

[Learn More at JEXtream.net](https://JEXtream.net)